- U. Producer shall provide a approved set of scales to weigh swine of market weight.
- V. Operate Bio-Security plan to the fullest extent.
- 6. LOSS OF SWINE, PRODUCER shall be responsible for the loss of any swine through theft. conversion, mysterious disappearance or inventory discrepancy. Such swine shall be valued at market hog price at time of notice of loss for a 240lb animal, and such value shall be deducted from any compensation due PRODUCER and PRODUCER shall be liable for any amounts remaining unpaid after deduction from PRODUCER'S compensation.
- 7. WAIVER OF PROPERTY DAMAGE. PRODUCER hereby waives any and all claims for recovery from for loss or damage to PRODUCER'S property caused directly or indirectly by the swine.
- 8. THIRD-PARTY CLAIMS. PRODUCER shall be responsible for any claims, damages or injuries caused by the swine delivered to the Facilities pursuant to this Agreement or PRODUCER'S management of the Facilities and hereby INDEMNIFIES AND HOLDS HARMLESS from any such claims, damages or injuries.
- 9. TRAINING. PRODUCER agrees to attend training sessions concerning Grow/Finish Production as designated by and follow all written and oral advice as given by Fieldman.
- 10. TRANSPORTATION. The Transportation of pigs to and from the Facilities shall be the responsibility of All labor shall be provided by the Producer.
- 11. INSURANCE. PRODUCER shall obtain and furnish with certificates of insurance evidencing liability insurance, including contractual coverage with minimum limits of \$500,000, for bodily injury and property damage.
- 12. FACILITY REQUIREMENTS. PRODUCER specifically agrees to provide and maintain in proper and sanitary working order, facilities meeting the following minimum requirements:
 - a. Confinement buildings providing 7.65 sq. ft. per pig space:
 - b. Make available to swine a minimum of one water nipple per every 10-15 swine
 - c. Have feeder space available the rate of one lid(or equivalent) per four swine.
 - d. Feeder openings must be adjustable to no more that 1/4 of an inch.
 - e. Portable loading and unloading equipment with a operating range of 16" to 72"
 - f. Proper alarm functions with a operating phone dialer.
 - Bio-Secure area . As defined in the production manual.
 - Telephone answering and Faxing capabilities will be required.
 - i. Operating curtain drops increase of power failure.

3